

Ruby - Bug #1506

irb

05/23/2009 07:27 PM - no6v (Nobuhiro IMAI)

Status:	Closed	Backport:
Priority:	Normal	
Assignee:		
Target version:		
ruby -v:	ruby 1.9.2dev (2009-05-23 trunk 23548) [i686-linux]	

Description

```
=begin
[ruby-dev:36198]
$ uname -a
Linux ribot 2.6.29-1-686 #1 SMP Fri Apr 17 14:35:16 UTC 2009 i686 GNU/Linux
$ ruby1.9 -v
ruby 1.9.2dev (2009-05-23 trunk 23548) [i686-linux]
$ echo $LANG
ja_JP.UTF-8
$ irb1.9 -f
irb(main):001:0> ENCODING
=> #Encoding:UTF-8
irb(main):002:0> :
/home/nov/ruby/lib/ruby/1.9.1/irb/ruby-lex.rb:539:in `block in lex_int2': invalid byte sequence in UTF-8 (ArgumentError)

irb(main):002:0> :
\x3a\xe3\xe3
:

irb1.9 -f --noreadline
irb(main):001:0> :
=> :

r23298 :
r23299 :.....

$ irb1.9 -f --readline
irb(main):001:0> RUBY_DESCRIPTION
=> "ruby 1.9.2dev (2009-04-27 trunk 23298) [i686-linux]"
irb(main):002:0> :
=> :
=end
```

History

#1 - 05/27/2009 01:40 AM - no6v (Nobuhiro IMAI)

```
=begin
:

From: Nobuhiro IMAI <redmine_at_ruby-lang.org>
Date: Sat, 23 May 2009 19:27:16 +0900

irb(main):002:0> :
\x3a\xe3\xe3

Readline.input= IO
:

$ cat rl.rb
```

-- coding: utf-8 --

```
p DATA.external_encoding
p DATA.getc
require "readline"
Readline.input = DATA
p Readline.readline(">> ", false)
END

```

ruby1.9 -v rl.rb
 ruby 1.9.2dev (2009-05-26 trunk 23576) [i686-linux]
 #Encoding:UTF-8
 ""

 ??
 "\xE3\xE3"

?? \xE3\xE3 \xE3

```
--
Nobuhiro IMAI nov@yo.rim.or.jp
Key fingerprint = F39E D552 545D 7C64 D690 F644 5A15 746C BD8E 7106

=end
```

```
#2 - 05/27/2009 02:47 AM - naruse (Yui NARUSE)
- Status changed from Open to Closed
- % Done changed from 0 to 100

=begin
Applied in changeset r23591.
=end
```