

Ruby - Bug #3832

Etc.sysconfig contains "\$(DESTDIR)" when ./configure is called with --sysconfdir=

09/15/2010 10:03 PM - Anonymous

Status:	Closed	Backport:
Priority:	Normal	
Assignee:		
Target version:	1.9.2	
ruby -v:	ruby 1.9.2p0	
Description		
<pre>=begin When the Ruby source files are configured for compilation with ./configure and the --sysconfdir= parameter is specified, the "ext/etc/extconf.h" file is generated with a SYSCONFDIR variable that contains "\$(DESTDIR)" literally, not expanded. For example: \$./configure --prefix=/usr --sysconfdir=/etc ... \$ make ... \$ grep SYSCONFDIR ext/etc/extconf.h #define SYSCONFDIR "\$(DESTDIR)/etc" This variable was introduced in r27667 and seems only used in "lib/rubygems/config_file.rb". Why not use Config::CONFIG['sysconfdir'] there (rbconfig is already required by rubygems)? Note: this was verified on Linux RHEL 5 with ruby-1.9.2-p0.tar.bz2. =end</pre>		

History

#1 - 09/16/2010 08:28 AM - nobu (Nobuyoshi Nakada)

```
=begin
Hi,

(10/09/15 22:03), Eric-Olivier Lamey wrote at [ruby-core:32394]:

  This variable was introduced in r27667 and seems only used in
  "lib/rubygems/config_file.rb". Why not use
  Config::CONFIG['sysconfdir'] there (rbconfig is already required by
  rubygems)?
```

It's determined at runtime on Windows.

```
--
Nobu Nakada

=end
```

#2 - 09/16/2010 08:37 AM - nobu (Nobuyoshi Nakada)

```
- Status changed from Open to Closed
- % Done changed from 0 to 100

=end

This issue was solved with changeset r29268.
Eric-Olivier, thank you for reporting this issue.
Your contribution to Ruby is greatly appreciated.
May Ruby be with you.

=end
```